

### 1. ELECTRICAL SPECIFICATIONS

Accuracy is indicated as  $\pm$  (% readings + no. of digits\*resolution) at  $23^{\circ}\text{C} \pm 5^{\circ}\text{C}$ , <80%RH

#### Voltage (RCD, LOOP, Phase sequence)

Range [V]	Resolution [V]	Accuracy
15 ÷ 460	1	$\pm(3.0\% \text{rdg} + 2\text{dgt})$

#### Continuity test on protective and equalizing conductors

Range [ $\Omega$ ]	Resolution [ $\Omega$ ]	Accuracy (*)
0.01 ÷ 9.99	0.01	$\pm(5.0\% \text{rdg} + 3\text{dgt})$
10.0 ÷ 99.9	0.1	
100 ÷ 1999	1	$\pm(10.0\% \text{rdg} + 5\text{dgt})$

(\*) calibrate the cables to null their resistance

Test current:  $> 200\text{mA DC}$  for  $R \leq 5\Omega$  (calibration included) ; Resolution for DC current :1mA

Open-circuit voltage:  $4\text{V} \leq V_0 \leq 12\text{V}$

#### Insulation resistance (DC voltage)

Test voltage[V]	Range [ $M\Omega$ ]	Resolution [ $M\Omega$ ]	Accuracy
50	0.01 ÷ 9.99	0.01	$\pm(2.0\% \text{rdg} + 2\text{dgt})$
	10.0 ÷ 49.9	0.1	
	50.0 ÷ 99.9	0.1	$\pm(5.0\% \text{rdg} + 2\text{dgt})$
100	0.01 ÷ 9.99	0.01	$\pm(2.0\% \text{rdg} + 2\text{dgt})$
	10.0 ÷ 99.9	0.1	
	100.0 ÷ 199.9	0.1	$\pm(5.0\% \text{rdg} + 2\text{dgt})$
250	0.01 ÷ 9.99	0.01	$\pm(2.0\% \text{rdg} + 2\text{dgt})$
	10.0 ÷ 99.9	0.1	
	100 ÷ 499	1	$\pm(5.0\% \text{rdg} + 2\text{dgt})$
500	0.01 ÷ 9.99	0.01	$\pm(2.0\% \text{rdg} + 2\text{dgt})$
	10.0 ÷ 199.9	0.1	
	200 ÷ 499	1	$\pm(5.0\% \text{rdg} + 2\text{dgt})$
1000	500 ÷ 999	1	$\pm(5.0\% \text{rdg} + 2\text{dgt})$
	0.01 ÷ 9.99	0.01	$\pm(2.0\% \text{rdg} + 2\text{dgt})$
	10.0 ÷ 199.9	0.1	
	200 ÷ 999	1	$\pm(5.0\% \text{rdg} + 2\text{dgt})$
1000 ÷ 1999	1	$\pm(5.0\% \text{rdg} + 2\text{dgt})$	

Open-circuit voltage: nominal test voltage  $-0\% +10\%$

Short circuit current:  $<6.0\text{mA}$  at 500V test voltage

Nominal test current:  $>1\text{mA}$  if load=  $1\text{k}\Omega \cdot V_{\text{nom}}$  ( $V_{\text{nom}}=50\text{V}, 100\text{V}, 250\text{V}, 500\text{V}, 1000\text{V}$ )

Safety protection: the display shows an error message for input voltage  $>10\text{V}$

#### Z Line (Line-Line, Line-Neutral, Line-PE)

Range [ $\Omega$ ]	Resolution [ $\Omega$ ]	Accuracy
0.00 ÷ 199.9 $m\Omega$ (*)	0.1 $m\Omega$ (*)	$\pm(5.0\% \text{rdg} + 1\text{m}\Omega)$ (*)
200 ÷ 1999 $m\Omega$ (*)	1 $m\Omega$ (*)	
0.01 ÷ 9.99 $\Omega$	0.01 $\Omega$	$\pm(5.0\% \text{rdg} + 3\text{dgt})$
10.0 ÷ 199.9 $\Omega$	0.1 $\Omega$	

(\*) By means of IMP57 optional accessory

Maximum test current: 5.81A (at 265V); 10.10A (at 457V)

Test voltage ranges: 100÷265V (Line-Neutral) / 100÷460V (Line-Line); 50/60Hz  $\pm 5\%$

Protection type: MCB (B, C, D, K), Fuse (gG, aM)

Insulation materials: PVC, Rubber butyl, EPR, XLPE

#### First fault current (IT systems)

Range (mA)	Resolution (mA)	Accuracy
0.1 ÷ 0.9	0.1	$\pm(5.0\% \text{rdg} + 1\text{dgt})$
1 ÷ 999	1	$\pm(5.0\% \text{rdg} + 3\text{dgt})$

Limit contact voltage (ULIM) : 25V, 50V



### RCD test (Molded case type)

RCD type: AC (⌚), A/F (⌚), B/B+ (⌚) – General (G), Selective (S) and Delayed (⌚)  
 Rated tripping currents (I<sub>ΔN</sub>): 6mA, 10mA, 30mA, 100mA, 300mA, 500mA, 650mA, 1000mA  
 Line-PE, Line-N voltage: 100V ±265V RCD type AC and A/F, 190V ±265V RCD type B/B+  
 Frequency: 50/60Hz ± 5%

### RCD tripping current (Molded case type – RCD General)

RCD type	I <sub>ΔN</sub>	Range I <sub>ΔN</sub> [mA]	Resolution [mA]	Accuracy I <sub>ΔN</sub>
AC, A/F, B/B+	6mA, 10mA	(0.2 ÷ 1.1) I <sub>ΔN</sub>	≤ 0.1 I <sub>ΔN</sub>	- 0%, +10% I <sub>ΔN</sub>
AC, A/F, B/B+	30mA ≤ I <sub>ΔN</sub> ≤ 300mA			- 0%, +5% I <sub>ΔN</sub>
AC, A/F	500mA ≤ I <sub>ΔN</sub> ≤ 650mA			

### RCD Molded type tripping time range [ms] (TT/TN system)

	x 1/2			x 1			x 2		x 5		AUTO			AUTO+		
	\	G	S	⌚	G	S	⌚	G	S	⌚	G	S	⌚	G	S	⌚
6mA	AC	999	999	999	999	999	999	160	210	50	150	✓	✓	310		✓
	A/F	999	999	999	999	999	999	160	210	50	150	✓	✓	310		✓
	B/B+	999	999	999	999	999	999							310		
10mA	AC	999	999	999	999	999	999	160	210	50	150	✓	✓	310		✓
	A/F	999	999	999	999	999	999	160	210	50	150	✓	✓	310		✓
	B/B+	999	999	999	999	999	999							310		
30mA	AC	999	999	999	999	999	999	160	210	50	150	✓	✓	310		✓
	A/F	999	999	999	999	999	999	160	210	50	150	✓	✓	310		✓
	B/B+	999	999	999	999	999	999							310		
100mA	AC	999	999	999	999	999	999	160	210	50	150	✓	✓	310		
	A/F	999	999	999	999	999	999	160	210	50	150	✓	✓	310		
	B/B+	999	999	999	999	999	999							310		
300mA	AC	999	999	999	999	999	999	160	210	50	150	✓	✓	310		
	A/F	999	999	999	999	999	999	160	210	50	150	✓	✓	310		
	B/B+	999	999	999	999	999	999							310		
500mA 650mA	AC	999	999	999	999	999	999	160	210	50	150	✓	✓	310		
	A/F	999	999	999	999	999	999	160	210					310		
	B/B+															
1000mA	AC	999	999	999	999	999	999	160	210							
	A/F	999	999	999	999	999	999									
	B/B+															

Resolution: 1ms, Accuracy: ±(2.0%rdg + 2dgt)

### RCD Molded type tripping time range [ms] (IT system) (\*)

	x 1/2			x 1			x 2		x 5		AUTO			AUTO+		
	\	G	S	⌚	G	S	⌚	G	S	⌚	G	S	⌚	G	S	⌚
6mA	AC	999	999	999	999	999	999	160	210	50	150	✓	✓	310		✓
10mA	A/F	999	999	999	999	999	999	160	210	50	150	✓	✓	310		✓
30mA	B/B+	999	999		999	999								310		✓
100mA 300mA	AC	999	999	999	999	999	999	160	210	50	150	✓	✓	310		
	A/F	999	999	999	999	999	999	160	210	50	150	✓	✓	310		
	B/B+	999	999		999	999										
500mA 650mA	AC	999	999	999	999	999	999	160	210	50	150	✓				
	A/F	999	999	999	999	999	999	160	210			✓				
	B/B+															
1000mA	AC	999	999		999	999		160	210							
	A/F	999	999		999	999										
	B/B+															

Resolution: 1ms, Accuracy: ±(2.0%rdg + 2dgt)

(\*) Selection RCD type A/F and type B/B+ available only for Norway country



### Test on earth leakage delay tester RCDs (with RCDX10 optional accessory)

RCD type: AC (⌚), A/F (⌚), B/B+ (⌚) – General (G), Selective (S) and Delayed (⌚)  
 Rated tripping currents (I<sub>ΔN</sub>): 0.3A ÷ 10A (type AC, A/F) ; 0.3A ÷ 3.0A (type B/B+)  
 Line-PE, Line-N voltage: 100V ÷265V RCD type AC and A/F, 190V ÷265V RCD type B/B+  
 Frequency: 50/60Hz ± 5%

### Earth leakage delay tester RCDs tripping current (RCD General)

RCD type	I <sub>ΔN</sub>	Range I <sub>ΔN</sub> [mA]	Resolution [mA]	Accuracy I <sub>ΔN</sub>
AC, A/F, B/B+	300mA ≤ I <sub>ΔN</sub> ≤ 1A	(0.3 ÷ 1.1) I <sub>ΔN</sub>	≤ 0.1 I <sub>ΔN</sub>	- 0%, +5% I <sub>ΔN</sub>
AC, A/F	1.1A ≤ I <sub>ΔN</sub> ≤ 10A			

### Earth leakage delay tester RCDs trip out time range [ms] (TT/TN system)

	\	x 1/2			x 1			x 2			x 5			AUTO			📈		
		G	S	⌚	G	S	⌚	G	S	⌚	G	S	⌚	G	S	⌚	G	S	⌚
<b>0.3A</b> ÷ <b>1.0A</b>	AC	999	999	999	999	999	999	200	250	50	150	✓	✓				310		
	A/F	999	999	999	999	999	999	200	250	50	150	✓	✓				310		
	B/B+	999	999	999	999	999	999										310		
<b>1.1A</b> ÷ <b>3.0A</b>	AC	999	999	999	999	999	999	200	250	50	150	✓	✓				310		
	A/F	999	999	999	999	999	999	200	250	50	150	✓	✓				310		
	B/B+	999	999	999	999	999	999										310		
<b>3.1A</b> ÷ <b>6.5A</b>	AC	999	999	999	999	999	999	200	250	50	150	✓	✓				310		
	A/F	999	999	999	999	999	999	200	250	50	150	✓	✓				310		
	B/B+																		
<b>6.6A</b> ÷ <b>10.0A</b>	AC	999	999	999	999	999	999	200	250										
	A/F	999	999	999	999	999	999	200	250										
	B/B+																		

Resolution: 1ms, Accuracy: ±(2.0%rdg + 2dgt)

### Earth leakage delay tester RCDs trip out time range [ms] (IT system) (\*)

	\	x 1/2			x 1			x 2			x 5			AUTO			📈		
		G	S	⌚	G	S	⌚	G	S	⌚	G	S	⌚	G	S	⌚	G	S	⌚
<b>0.3A</b> ÷ <b>3.0A</b>	AC	999	999	999	999	999	999	200	250	50	150	✓	✓				310		
	A/F	999	999	999	999	999	999	200	250	50	150	✓	✓						
	B/B+																		
<b>3.1A</b> ÷ <b>6.5A</b>	AC	999	999	999	999	999	999	200	250	50	150	✓	✓				310		
	A/F	999	999	999	999	999	999	200	250	50	150	✓	✓						
	B/B+																		
<b>6.6A</b> ÷ <b>10.0A</b>	AC	999	999	999	999	999	999	200	250										
	A/F	999	999	999	999	999	999	200	250										
	B/B+																		

Resolution: 1ms, Accuracy: ±(2.0%rdg + 2dgt)

(\*) Selection RCD type A/F and type B/B+ available only for Norway country

### NoTripTest – Non-trip earth loop impedance

Test voltage: 100÷265V (Line-PE), 50/60Hz ± 5%

### NoTripTest – Systems with Neutral wire

Range [Ω]	Resolution [Ω]	Accuracy (*)
0.01 ÷ 9.99	0.01	±(5% reading + N/10)
10.0 ÷ 199.9	0.1	±(5% reading + N)
200 ÷ 1999	1	±(5% reading + 3N)

(\*) If I<sub>ΔN</sub> < 30mA, test current = I<sub>ΔN</sub>/2 and N[Ω]=30/I<sub>ΔN</sub>; if I<sub>ΔN</sub> ≥ 30mA, test current < 15mA and N=1Ω

### NoTripTest – Systems without Neutral wire

Range [Ω]	Resolution [Ω]	Accuracy (*)
1 ÷ 1999	1	-0%, +(5.0% lettura +N)

(\*) if I<sub>ΔN</sub> < 30mA, test current = I<sub>ΔN</sub>/2 and N[Ω]=(10x30)/I<sub>ΔN</sub> Ω; if I<sub>ΔN</sub> ≥ 30mA, test current I<sub>ΔN</sub>/2 and N[Ω]=(3x30)/I<sub>ΔN</sub>



### Contact voltage (RCD and NoTripTest)

Range [V]	Resolution [V]	Accuracy
0 ÷ U <sub>lim</sub>	0.1	-0%, +(5.0% rdg + 3V)

### Contact voltage (EARTH test – TT system)

Range [V]	Resolution [V]	Accuracy
0 ÷ 99.9	0.1	-0%, +(5.0% rdg + 3V)

### Contact voltage (EARTH test – TN system)

Range [V]	Resolution [V]	Accuracy
0 ÷ 99.9	0.1	-0%, +(5.0% rdg + 3V)
100 ÷ 999	1	

### Ground resistance with 3-wire method

Range [Ω]	Resolution [Ω]	Accuracy (*)
0.01 ÷ 9.99	0.01	±(5.0% rdg + 3dgt)
10.0 ÷ 99.9	0.1	
100 ÷ 999	1	
1.00k ÷ 49.99k	0.01k	

Test current: <10mA – 77.5Hz, Open-circuit voltage: < 20Vrms

(\*) Add 5% to the accuracy if the probe resistances (R<sub>s</sub> or R<sub>h</sub>) > 100 x R<sub>meas</sub>

### Soil resistivity with 4-wire Wenner method

Range [Ωm]	Resolution [Ωm]	Accuracy (*)
0.06 ÷ 9.99	0.01	±(5.0% rdg + 3dgt)
10.0 ÷ 99.9	0.1	
100 ÷ 999	1	
1.00k ÷ 9.99k	0.01k	
10.0k ÷ 99.9k	0.1k	
100k ÷ 999k	1k	
1.00M ÷ 3.14M	0.01M	

(\*) with distance d=10m, Distance "d" range: 1 ÷ 10m

Test current: <10mA – 77.5Hz, Open-circuit voltage: < 20Vrms

### Phase sequence rotation with 1-wire method

Voltage range P-N, P-PE[V]	Frequency range
100 ÷ 265	50Hz/60Hz ± 5%

Measurement is only carried out by direct contact with metal live parts (**not on insulation sheath**)

### Voltage drop on main power lines (ΔV%)

Range (%)	Resolution (%)	Accuracy
0 ÷ 100	0.1	±(10.0% rdg + 4dgt)

### Leakage current (by HT96U optional clamp transducer)

Range [mA]	Resolution [mA]	Accuracy
0.5 ÷ 999.9	0.1	±(5.0% rdg + 2dgt)

### Environmental parameters (AUX function)

Parameter	Range	Resolution	Accuracy
Temperature [°C]	-20°C ÷ 80°C	0.1 °C	±(2.0%rdg+2dgt)
Temperature [°F]	-4°F ÷ 176°F	0.1 °F	
Relative humidity [%HR]	0 ÷ 100%HR	0.1% UR	
DC output voltage	0.1mV ÷ 1.0V	0.1mV	
Illuminance [Lux]	0.001Lux ÷ 20.00 Lux (*)	0.001 ÷ 0.02 Lux	
	0.1 Lux ÷ 2000 Lux (*)	0.1 ÷ 2 Lux	
	1 Lux ÷ 20 kLux (*)	1 ÷ 20 Lux	

(\*) Accuracy of HT53 lux probe is according to Class AA



## Measurement of main parameters and harmonics (PQA)

### AC TRMS Voltage

Range [V]	Resolution [V]	Accuracy
15.0 ÷ 459.9	0.1V	±(1.0%rdg + 1dgt)

Allowed crest factor ≤ 1,5 ; Frequency: 42.5 ÷ 69.0 Hz

### Frequency

Range [Hz]	Resolution [Hz]	Accuracy
42.5 ÷ 69.0	0.01	±(2.0%rdg + 2dgt)

Allowed voltage: 15.0 ÷ 459.9V ; Allowed current: 5%FS clamp ÷ FS clamp

### AC TRMS Current

FS clamp	Range [A]	Resolution [A]	Accuracy
≤ 10A	5% FS ÷ 9.99	0.01	1Ph: ±(1.0%rdg + 3 dgt) 3Ph: ±(2.0%rdg + 5 dgt)
10A ≤ FS ≤ 200	5% FS ÷ 199.9	0.1	
200A ≤ FS ≤ 3000	5% FS ÷ 2999	1	

Range: 5 ÷ 999.9 mV; Values under 5mV are zeroed

Allowed crest factor ≤ 3; Frequency: 42.5 ÷ 69.0 Hz

### Active power (@ 230V in 1Ph systems, 400V in 3Ph systems, cosφ=1, f=50.0Hz)

FS clamp	Range [kW]	Resolution [kW]	Accuracy
≤ 10A	0.000 ÷ 9.999	0.001	1Ph: ±(2.0%rdg + 5 dgt) 3Ph: ±(2.5%rdg + 8 dgt)
10A ≤ FS ≤ 200	0.00 ÷ 999.99	0.01	
200A ≤ FS ≤ 1000	0.0 ÷ 999.9	0.1	
1000A ≤ FS ≤ 3000	0 ÷ 9999	1	

### Reactive power (@ 230V in 1Ph systems, 400V in 3Ph systems, cosφ=0, f=50.0Hz)

FS clamp	Range [kVAr]	Resolution [kVAr]	Accuracy
≤ 10A	0.000 ÷ 9.999	0.001	1Ph: ±(2.0%rdg + 7 dgt) 3Ph: ±(3.0%rdg + 8 dgt)
10A ≤ FS ≤ 200	0.00 ÷ 999.99	0.01	
200A ≤ FS ≤ 1000	0.0 ÷ 999.9	0.1	
1000A ≤ FS ≤ 3000	0 ÷ 9999	1	

### Power factor (@ 230V in 1Ph systems, 400V in 3Ph systems, f=50.0Hz)

Range	Resolution	Accuracy
0.70c ÷ 1.00 ÷ 0.70i	0.01	±(4.0%rdg + 10dgt) if I ≤ 10%FS ±(2.0%rdg + 3dgt) if I > 10%FS

### cosφ (@ 230V in 1Ph systems, 400V in 3Ph systems, f=50.0Hz)

Range	Resolution	Accuracy
0.70c ÷ 1.00 ÷ 0.70i	0.01	±(4.0%rdg + 10dgt) if I ≤ 10%FS ±(1.0%rdg + 7dgt) if I > 10%FS

### Voltage harmonics (@ 230V in 1Ph systems, 400V in 3Ph systems, f=50.0Hz)

Range [%]	Resolution [%]	Order	Accuracy
0.1 ÷ 100.0	0.1	01 ÷ 25	±(5.0%rdg + 5dgt)

Frequency of fundamental: 42.5 ÷ 69.0 Hz, DC accuracy not declared

### Current harmonics (f=50Hz)

Range [%]	Resolution [%]	Order	Accuracy
0.1 ÷ 100.0	0.1	01 ÷ 9	±(5.0%rdg + 5dgt)
		10 ÷ 17	±(10.0%rdg + 5dgt)
		18 ÷ 25	±(15.0%rdg + 10dgt)



## 2. GENERAL SPECIFICATIONS

### DISPLAY AND MEMORY:

Features:	Touch screen, color graphic LCD, 320x240mm
Memory:	999 locations, 3 marker levels
Communication:	Optical-USB and built-in WiFi

### POWER SUPPLY:

Batteries:	6 x 1.2V(rechargeable) type AA or 6 x 1.5V type AA
Battery life:	> 500 test for each function
Auto Power OFF:	after 5 min of idleness (disabled)

### MECHANICAL FEATURES:

Dimensions (L x W x H):	225 x 165 x 75mm
Weight (included batteries):	1.2kg

### WORKING ENVIRONMENTAL CONDITIONS:

Reference temperature:	23°C ± 5°C
Working temperature:	0°C ÷ 40°C
Allowed relative humidity:	<80%RH
Storage temperature:	-10°C ÷ 60°C
Storage humidity:	<80%RH

### TEST VERIFIES REFERENCE STANDARDS:

Continuity test with 200mA:	IEC/EN61557-4
Insulation resistance:	IEC/EN61557-2
Earth resistance:	IEC/EN61557-5
Fault loop impedance:	IEC/EN61557-3
RCD test:	IEC/EN61557-6
Multifunction:	IEC/EN61557-10
Prospective short circuit current:	EN60909-0
Earth resistance on TN systems:	EN61936-1 + EN50522

### GENERAL REFERENCE STANDARDS:

Safety of measuring instruments:	IEC/EN61010-1, IEC/EN61010-031, IEC/EN61010-2-032
Product type standard:	IEC/EN61557-1
Technical documentation :	IEC/EN61187
Insulation:	double insulation
Pollution degree:	2
Encapsulation :	IP40
Overvoltage category:	CAT IV 300V~ (to ground), max 415V between inputs
Max height of use:	2000m

**This instrument satisfies the requirements of Low Voltage Directive 2014/35/EU (LVD),  
EMC Directive 2014/35/EU and Directive RED 2014/53/EU  
This instrument satisfies the requirements of European Directive 2011/65/EU (RoHS) and 2012/19/EU  
(WEEE)**

