



PROFESSIONAL MULTIMETER WITH BUILT-IN THERMAL CAMERA



CODE **HROO0MER**

MERCURY

PROFESSIONAL MULTIMETER
WITH BUILT-IN THERMAL
CAMERA



→ **TRMS**
AC+DC

CAT IV
600V



AUTO
RANGE

MULTIMETER

- > **TRMS** measurement
- > **AC, DC, AC+DC current** up to **10A**
- > **DC/AC/AC+DC TRMS current** with standard/flexible external clamp transducers
- > **AC, DC, AC+DC voltage** up to **1000V**
- > **Resistance, Continuity test**
- > **Frequency and Duty Cycle**
- > **Capacity and Temperature** with **K probe**, **Diode test**
- > **NCV sensor** for **contactless** AC voltage detection
- > Data **HOLD, MAX/MIN/PEAK, REL** function

THERMAL CAMERA

- > **Built-in thermal camera 80x80px**
- > **Infrared temperature measurement**
- > **Laser pointer** and white **LED torch**
- > **Bluetooth** for connection to mobile devices
- > Dedicated **HTMercury APP***

* The **HTMercury** app can be downloaded for free on Apple Store™ and Google Play™



TECHNICAL DATA SHEET

TECHNICAL SPECIFICATIONS

Counts	6000
DC, AC TRMS, AC+DC TRMS voltage	up to 1000V
DC, AC TRMS, AC+DC TRMS current	up to 10A
AC and AC+DC TRMS current using standard clamp transducers	●
AC TRMS current using a F3000U flexible clamp transducer	up to 3000AC
"Volsense" for AC voltage detection	●
Resistance	●
Continuity with buzzer	●
Temperature probe type K	●
Diode test	●
Capacity	●
Frequency	●
Relative Measurement	●
MAX/MIN	●
PEAK	●
Data HOLD	●
Bargraph	●
Backlighting	●
Datalogger and graph	●
Auto Power OFF	●
IR sensor resolution	80 x 80 pxl
Infrared temperature measuring range	-20°C ÷ 260°C / -4°F ÷ 500°F
Thermal sensitivity / NETD	< 0.1°C @ 30°C
NETD	< 100mK
Spectral range	8 ÷ 14µm
IFOV	4.53 mrad
Field of view (FOV)	21° x 21°
Lens	7.5mm
3 cursors: Central, Min, Max	●
8 standard + 10 customisable colour palettes	5 standard, non-customisable
Readings in °C, °F, °K	●
Built-in white light torch	●
Laser pointer	Class 2

GENERAL SPECIFICATIONS

Dimensions (L x W x H)	190 x 75 x 55mm
Weight (batteries included)	555g
Operating temperature	from 5°C to 40°C
Operating humidity	<80% RH
Protection rating	IP65
Power supply	2 x rechargeable Li- ION batteries

ACCESSORIES

STANDARD ACCESSORIES

TK101	Wire K-type probe for measuring temperature
T10	Adapter for connecting TK temperature probes
F3000U	Flexible clamp with full scale 30/300/3000A AC and banana connectors
4324-2	Pair of professional leads, red/black 2/4mm 90°
AOMCY	Multiplug power supply and charging base
BATMCY	Rechargeable Li-ION battery, 2 pieces
BOMCY	Carry bag
8GB memory card	
Complete user manual and HTMercury APP available online	
Calibration report	
Quick start guide	

OPTIONAL ACCESSORIES

TK107	K probe for air and gas temperature
TK108	K probe for semi-solid substance temperature
TK109	K probe for liquid temperature
TK110	K probe for surface temperatures
TK111	K probe for surface temperatures with 90° tip
HT4006	Standard clamp transducer DC/AC 40-400A/IV
HT96U	Standard clamp transducer AC 1-100-1000A/IV
HT97U	Standard clamp transducer AC 10-100-1000A/IV
HT98U	Standard clamp transducer DC 1000A/IV
NOCANBA	Adapter for connecting standard clamps with custom HT connector

HT ITALIA S.R.L.

Via della Boaria, 40 48018 Faenza (RA) Italy

T +39 0546 621002 | F +39 0546 621144

M vendite@ht-instruments.com | ht-instruments.com