

1. ELECTRICAL SPECIFICATIONS

Accuracy indicated as \pm [%reading + (number dgts * resolution)] at 23°C \pm 5°C, <80%RH.

DC CURRENT

Range	Resolution	Accuracy	Overload protection
40.00A	0.01A	$\pm(2.5\%rdg+10dgt)$	400A DC/ACrms
400.0A	0.1A	$\pm(2.8\%rdg+8dgt)$	

AC TRMS CURRENT

Range	Resolution	Accuracy (50Hz \div 60Hz)	Accuracy (61Hz \div 400Hz)	Overload protection
40.00A	0.01A	$\pm(2.5\%rdg+10dgt)$	$\pm(2.8\%rdg+10dgt)$	400A DC/ACrms
400.0A	0.1A	$\pm(2.8\%rdg+8dgt)$	$\pm(2.8\%rdg+8dgt)$	

For not sinusoidal waveforms the frequency range is: 50Hz \div 60Hz
INRUSH feature range (40A): 3A \div 40A, 50/60Hz, Accuracy: $\pm 10\%rdg$
INRUSH feature range (400A): 10A \div 400A, 50/60Hz, Accuracy: $\pm 10\%rdg$
INRUSH response time: 100ms

2. GENERAL SPECIFICATIONS

Display:

- LCD, 3 $\frac{3}{4}$ dgt, 4000 counts + decimal point + backlight

Features:

- Data HOLD, ZERO, INRUSH CURRENT
- AC voltage detection without contact (NCV): range 200V \div 1000V, 50/60Hz

Frequency rate:

- 3 times/s
- Conversion: TRMS

Environmental conditions:

- Working temperature/humidity: 5°C \div 40°C, <80%RH
- Storage temperature/humidity: -20°C \div 60°C, <80%RH

General characteristics:

- Max height of use: 2000m
- Pollution degree: 2
- Insulation: double insulation
- Max diameter of conductor: 20mm

Power supply:

- 2 x 1.5V batteries type AAA LR03
- Battery life: ca 85h (with backlight), ca 240h (without backlight)
- Auto Power OFF: after 15min of idleness

Mechanical characteristics:

- Dimensions (L x W x H): 155 x 60 x 25mm
- Weight (included batteries): 140g
- Mechanical protection: IP30

Reference guidelines:

- Safety : IEC/EN61010-1, CAT III 300V, EMC: IEC/EN61326-1

This product conforms to the prescriptions of the European LVD directive 2014/35/EU and to EMC directive 2014/30/EU





HT7005

Rel. 2.00 of 13/09/24

Compact DC/AC TRMS clamp with INRUSH feature

Page 2 of 2



HT ITALIA SRL
Via della Boaria, 40
48018 - Faenza (RA) - Italy
T +39 0546 621002 | F +39 0546 621144
M export@ht-instruments.com | ht-instruments.com

WHERE
WE ARE

