

1. ELECTRICAL SPECIFICATIONS

Accuracy calculated as $\pm[\% \text{reading} + (\text{num dgt} * \text{resolution})]$ ta 18°C ÷ 28°C, <75%RH

DC VOLTAGE

Range	Resolution	Accuracy	Input impedance	Overload protection
600.0mV	0.1mV	$\pm(0.09\% \text{rdg} + 5 \text{dgt})$	>10M Ω	1000VDC/ACrms
6.000V	0.001V			
60.00V	0.01V			
600.0V	0.1V	$\pm(0.2\% \text{rdg} + 5 \text{dgt})$		
1000V	1V			

AC TRMS VOLTAGE

Range	Resolution	Accuracy (*)		Overload protection
		50Hz ÷ 60Hz	61Hz ÷ 1kHz	
6.000V	0.001V	$\pm(0.8\% \text{rdg} + 5 \text{dgt})$	$\pm(2.4\% \text{rdg} + 5 \text{dgt})$	1000VDC/ACrms
60.00V	0.01V			
600.0V	0.1V			
1000V	1V			

(*) Accuracy specified from 5% to 100% of measurement range and sinusoidal waveform ; Input impedance: >9M Ω

Accuracy PEAK function: $\pm 10\% \text{rdg}$, PEAK response time: 1ms

For not sinusoidal waveforms the accuracy is: $\pm(10\% \text{rdg} + 10 \text{dgt})$

NCV sensor for AC voltage detection: LEN on for phase-PE voltage within 100V and 1000V, 50/60Hz

AC+DC TRMS VOLTAGE

Range	Resolution	Accuracy (*) 50Hz ÷ 1kHz	Input impedance	Overload protection
6.000V	0.001V	$\pm(2.4\% \text{rdg} + 20 \text{dgt})$	>10M Ω	1000VDC/ACrms
60.00V	0.01V			
600.0V	0.1V			
1000V	1V			

DC CURRENT

Range	Resolution	Accuracy	Overload protection
600.0 μ A	0.1 μ A	$\pm(0.9\% \text{rdg} + 5 \text{dgt})$	Fast Fuse 800mA/1kV (inputs mA, μ A)
6000 μ A	1 μ A		
60.00mA	0.01mA		
600.0mA	0.1mA	$\pm(0.9\% \text{rdg} + 8 \text{dgt})$	Fast Fuse 10A/1kV (input 10A)
10.00A	0.01A	$\pm(1.5\% \text{rdg} + 8 \text{dgt})$	

AC TRMS CURRENT

Range	Resolution	Accuracy (*) (50Hz ÷ 1kHz)	Overload protection
600.0 μ A	0.1 μ A	$\pm(1.2\% \text{rdg} + 5 \text{dgt})$	Fast Fuse 800mA/1kV (inputs mA, μ A)
6000 μ A	1 μ A		
60.00mA	0.01mA		
600.0mA	0.1mA		
10.00A	0.01A	$\pm(1.5\% \text{rdg} + 5 \text{dgt})$	Fast Fuse 10A/1kV (input 10A)

(*) Accuracy specified from 5% to 100% of measurement range and sinusoidal waveform

Accuracy PEAK function: $\pm 10\% \text{rdg}$, PEAK response time: 1ms;

For not sinusoidal waveforms the accuracy is: $\pm(10\% \text{rdg} + 10 \text{dgt})$

AC+DC TRMS Current: accuracy (50Hz÷1kHz): $\pm(3.0\% \text{reading} + 20 \text{dgt})$



DC CURRENT WITH STANDARD TRANSDUCERS CLAMPS

Range	Output ratio	Resolution	Accuracy (*)	Overload protection
1000mA	1000mV/1000mA	1mA	±(0.8%rdg + 5dgt)	1000VDC/ACrms
10A	100mV/1A	0.01A		
40A (**)	10mV/1A	0.01A		
100A	10mV/1A	0.1A		
400A (**)	1mV/1A	0.1A		
1000A	1mV/1A	1A		

(*) Accuracy of the only instrument without clamp; (**) With transducer clamp HT4006

AC, AC+DC TRMS CURRENT WITH STANDARD TRANSDUCERS CLAMPS

Range	Output ratio	Resolution	Accuracy (*)		Overload protection
			(50Hz ÷ 60Hz)	(61Hz ÷ 1kHz)	
1000mA	1V/1mA	1mA	±(0.8%rdg + 5dgt)	±(2.4%rdg+5dgt)	1000VDC/ACrms
10A	100mV/1A	0.01A			
40A (**)	10mV/1A	0.01A			
100A	10mV/1A	0.1A			
400A (**)	1mV/1A	0.1A			
1000A	1mV/1A	1A			

(*) Accuracy of the only instrument without clamp; (**) With transducer clamp HT4006

AC TRMS CURRENT WITH FLEXIBLE CLAMP (F3000U)

Range	Output ratio	Resolution	Accuracy (*)		Overload protection
			(50Hz ÷ 60Hz)	(61Hz ÷ 1kHz)	
30A	100mV/1A	0.01A	±(0.8%rdg+5dgt)	±(2.4%rdg+5dgt)	1000VDC/ACrms
300A	10mV/1A	0.1A			
3000A	1mV/1A	1A			

(*) Accuracy of the only instrument without clamp; Accuracy specified from 5% to 100% of measurement range

DIODE TEST

Range	Test current	Open voltage
	<1.5mA	3.3VDC

FREQUENCY (Electrical circuits)

Range	Resolution	Accuracy	Overload protection
40.00Hz ÷ 10kHz	0.01Hz ÷ 0.001kHz	±0.5%rdg	1000VDC/ACrms

Sensitivity: 2Vrms

FREQUENCY (Electronic circuits)

Range	Resolution	Accuracy	Overload protection
60.00Hz	0.01Hz	±(0.09%rdg+5dgt)	1000VDC/ACrms
600.0Hz	0.1Hz		
6.000kHz	0.001kHz		
60.00kHz	0.01kHz		
600.0kHz	0.1kHz		
1.000MHz	0.001MHz		
10.00MHz	0.01MHz		

Sensitivity: >2Vrms (@ 20% ÷ 80% duty cycle) and f<100kHz; >5Vrms (@ 20% ÷ 80% duty cycle) and f>100kHz



DUTY CYCLE

Range	Resolution	Accuracy	Overload protection
5.0% ÷ 95.0%	0.1%	$\pm(1.2\%rdg+2dgt)$	1000VDC/ACrms

Pulse frequency range: 40Hz ÷ 10kHz, Impulse amplitude: $\pm 5V$ (100 μ s ÷ 100ms)

RESISTANCE AND CONTINUITY TEST

Range	Resolution	Accuracy	Buzzer	Overload protection
600.0 Ω	0.1 Ω	$\pm(0.5\%rdg+10dgt)$	<50 Ω	1000VDC/ACrms
6.000k Ω	0.001k Ω	$\pm(0.5\%rdg+5dgt)$		
60.00k Ω	0.01k Ω			
600.0k Ω	0.1k Ω			
6.000M Ω	0.001M Ω			
60.00M Ω	0.01M Ω	$\pm(2.5\%rdg+10dgt)$		

CAPACITANCE

Range	Resolution	Accuracy	Overload protection
60.00nF	0.01nF	$\pm(1.5\%rdg + 20dgt)$	1000VDC/ACrms
600.0nF	0.1nF	$\pm(1.2\%rdg + 8dgt)$	
6.000 μ F	0.001 μ F	$\pm(1.5\%rdg + 8dgt)$	
60.00 μ F	0.01 μ F	$\pm(1.2\%rdg + 8dgt)$	
600.0 μ F	0.1 μ F	$\pm(1.5\%rdg + 8dgt)$	
6000uF	1uF	$\pm(2.5\%rdg + 20dgt)$	

TEMPERATURE WITH TYPE K PROBE

Range	Resolution	Accuracy (*)	Overload protection
-40°C ÷ 600°C	0.1°C	$\pm(1.5\%rdg+3^{\circ}C)$	1000VDC/ACrms
600°C ÷ 1000°C	1°C		
-40°F ÷ 600°F	0.1°F	$\pm(1.5\%rdg+5.4^{\circ}F)$	
600°F ÷ 1800°F	1°F		

(*) Accuracy referred to instrument without probe

Specified accuracy with stable environmental temperature at $\pm 1^{\circ}C$, For long-lasting measurements, reading increases by 2°C

INFRARED TEMPERATURE

Detector type	UFPA (80x80pxl, 34 μ m)
Spectral range	8 ÷ 14 μ m
Field of View (FOV) / Lens	21° x 21° / 7.5mm
IFOV (@1m)	4.53mrad
Thermal sensitivity	<0.1 °C @ 30°C (86°F) / 100mK
Focusing	Automatic
Minimum focal distance	0.5m
Image frequency	50Hz
Temperature unit	°C, °F, K
Colour palettes	4 (Iron, Rainbow, Grey, Grey Inverted)
Laser beam	Class 2 according with IEC 60825-1
Integrated illuminator	White LED light
Emissivity correction	0.01 ÷ 1.00
Measurement cursors	3 (Fixed, Max, Min)
Temperature range	-20°C ÷ 260°C (-4°F ÷ 500°F)
Accuracy	$\pm 3^{\circ}C(5.4^{\circ}F)$ or $\pm 3\%rdg$ (@ env temp: 10°C ÷ 35°C, object temp >0°C)



3. GENERAL SPECIFICATIONS

Display:

- Colour TFT, 6000 counts, sign, decimal point and bargraph
- Automatic polarity indication
- "OL" over range indication
- Response time: 3/s
- Conversion: TRMS

Features:

- Data HOLD
- MAX/MIN/PEAK (1ms)
- RANGE
- REL
- DATA LOGGER (internal memory): max 16 recordings, sample interval: 1s ÷ 15min, recording duration max 10 hours
- Fuse protection: F10A/1000V, 10 x 38mm (input **10A**), F800mA/1000V, 6 x 32mm (input **mA μ A**)
- Laser beam
- White LED illuminator
- MEMORY: saved screenshots/pics in a micro SD card, BMP format, ca 23kscreenshots (@ 8GB card)
- Bluetooth connection (BLE 4.0) for connection to mobile devices (by means **HTMercury APP**)
- Auto Power OFF after 15, 30, 60min of idleness (disable)

Environmental conditions:

- Operating Temperature/Humidity: 5 °C ÷ 40 °C (41 °F ÷ 104 °F), <80%RH
- Storage Temperature/Humidity: -20 °C ÷ 60 °C (-4 °F ÷ 140 °F), <80%RH

General informations:

- Altitude max of use: 2000m
- Pollution degree: 2
- Insulation: double insulation

Mains supply:

- 1x7.4V rechargeable Li-ION battery, 1500mAh
- Battery rechargeable adapter: 100/240VAC, 50/60Hz, 12VDC, 3A
- Recharging time: ca 2 hours
- Battery life: ca 8hours (Bluetooth inactive), ca 7hours (Bluetooth active)

Mechanical specifications

- Dimensions ((L x W x H): 190 x 75 x 55mm
- Weight (included battery) : 555g
- Mechanical protection : IP65

Reference guidelines:

- Safety : IEC/EN61010-1
- EMC : IEC/EN61326-1
- Measurement category : CAT IV 600V – CAT III 1000V

This product conforms to the prescriptions of the European directive on low voltage 2014/35/EU and to EMC directive 2014/30/EU

This product conforms to the prescriptions of the European directive 2011/65/EU (RoHS) and the European directive 2012/19/EU (WEEE)

