



HTFLEX315

Rel. 1.00 of 06/05/25

Flexible clamp meter 6000A AC TRMS

Pag 1 of 1

1. ELECTRICAL SPECIFICATIONS

Measurement range:	6000A AC _{RMS}
Output signal (@ 1000A _{RMS} , 50Hz):	85mV AC
Output impedance (@ 50Hz):	89Ω
Min allowed load impedance:	100kΩ
Accuracy:	class 1-A1 compliance IEC 61869-10
Frequency range:	50Hz ÷ 60Hz
Measurement category:	CAT III 1000V, CAT IV 600V AC
Insulation:	double insulation
Pollution degree	2 according to IEC/EN610101-1

2. GENERAL SPECIFICATIONS

Flexible cord length:	250mm
Maximum conductor diameter:	50mm
Instrument connection cable length:	2m
Flexible cord diameter:	8.3mm ± 0.2mm
Flexible cord material:	Thermoplastic polyurethane UL94-V0
Flexible cord blocking:	interlocking
Output connector:	HT custom, 5 poles
Mechanical protection:	IP65
Weight:	approx: 170g
Operating temperature:	-20°C ÷ +80°C
Storage temperature:	-40°C ÷ +90°C
Operating humidity	15%RH ÷ 85%RH without condense

3. REFERENCE GUIDELINES

Safety:	IEC/EN61010-1, IEC/EN61010-2-032
---------	----------------------------------

This instrument complies with the requirements of the European Low Voltage Directives 2014/35/EU (LVD). This instrument satisfies the requirements of 2011/65/EU+2015/863/EU (RoHS) directive and 2012/19/EU (WEEE) directive



HT ITALIA SRL
Via della Boaria, 40
48018 - Faenza (RA) - Italy
T +39 0546 621002 | F +39 0546 621144
M export@ht-instruments.com | ht-instruments.com

WHERE
WE ARE

